

INDUSTRIAL

SPECIFICATIONS

	EB3000c	EB4000X	EB5000X	EB6500X	EB10000
Engine	Honda GX200	Honda iGX270	Honda iGX390	Honda iGX390	Honda GX630
	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled	Twin cylinder, overhead valve, air-cooled
Displacement	196cc	270cc	389cc	389cc	688cc
AC output	120V 3000W max. (25.0A) 2600W rated (21.7A)	120/240V 4000W max. (33.3/16.7A) 3600W rated (30/15A)	120/240V 5000W max. (41.7/20.8A) 4500W rated (37.5/18.8A)	120/240V 6500W max. (54.1/27.1A) 5500W rated (45.8/22.9A)	120/240V 10000W max. (83.8/41.6A) 9000W rated (75/37.5A)
iAVR AC output	N/A	5000W (41.7/20.8A) for 10 sec.	7000W (58.3/29.2A) for 10 sec.	7000W (58.3/29.2A) for 10 sec.	N/A
Receptacles	D, F	C(2), F, G	C(2), F, H	C(2), F, H	C(2), F, H, I
DC output	N/A	N/A	N/A	N/A	N/A
Starting system	Recoil	Recoil	Recoil	Recoil	Electric
Fuel tank capacity	2.6 gal.	6.2 gal.	6.2 gal.	6.2 gal.	8.1 gal.
Run time per tankful	6.1 hrs. @ rated load, 9.39 hrs. @ 1/2 load	10.1 hrs. @ rated load, 16.0 hrs. @ 1/2 load	8.1 hrs. @ rated load, 11.2 hrs. @ 1/2 load	6.9 hrs. @ rated load, 10.4 hrs. @ 1/2 load	4.6 @ rated load, 7.2 hrs @1/2 load
Dimensions (L x W x H)	17.5" x 15.8" x 18.9"	41.9" x 27.2" x 29.2"	41.9" x 27.2" x 29.2"	41.9" x 27.2" x 29.2"	55.9" x 26.7" x 35.1"
Noise level	68 dB @ rated load 97 LwA ^{††}	71 dB @ rated load 97 LwA ^{††}	72 dB @ rated load 99 LwA ^{††}	73 dB @ rated load 100 LwA ^{††}	76 dB @ rated load 104 LwA ^{††}
Dry weight	71 lbs.	185 lbs.	214 lbs.	220 lbs.	403 lbs.

FEATURES

	EB3000c	EB4000X	EB5000X	EB6500X	EB10000
Honda OHV engine	•	•	•	•	•
Electric start/Remote start option					
Oil Alert®	•	•	•	•	•
Auto Throttle®		•	•	•	•
Eco-Throttle™ (load dependent operation)					
Electronic ignition	•	•	•	•	•
Simultaneous AC/DC use					
Circuit breakers	•	•	•	•	•
Fuel gauge	•	•	•	•	•
i-Monitor					•
Wheel kit standard		•	•	•	•
iAVR		•	•	•	•
DAVR		•	•	•	•
CycloConverter™	•				
Inverter					
One switch for engine/fuel valve on/off					
Full tubing frame for protection	•	•	•	•	•
USDA-qualified spark arrester/muffler	•	•	•	•	•
Fully enclosed for quieter operation					
120/240V selector switch		•	•	•	•
GFCI/neutral bond	•	•	•	•	•
Residential warranty	3 Years	3 Years	3 Years	3 Years	3 Years
Commercial warranty	3 Years	3 Years	3 Years	3 Years	3 Years

††LwA is an international noise level measurement that uses a weighting factor to reflect noise "tonality" in addition to the sound power (dBA) level.

Receptacle Key

RECEPTACLE	DESCRIPTION	PLUG #	RECEPTACLE	DESCRIPTION	PLUG #
B	15A 125V Duplex	5-15P	D	20A 125V GFCI Duplex	5-20P
C	20A 125V Duplex	5-15P or 5-20P	E	20A 125V Locking Plug	L5-20P