

WINGCO®

Quality Generators Since 1927



HPS12000HE



Engine:

- Honda GX630 V-Twin OHV
- EPA certified design for use with gasoline, LP and natural gas
- Commercial grade engine with cast iron cylinder sleeves
- 3 year warranty
- Special carburetor and secondary gas regulator allows the engine to operate on the most convenient fuel - gasoline, LP or natural gas
- Maintenance-free electronic ignition system
- Low oil protection helps prevent costly repairs and downtime

Generator End:

- 100% copper windings - longer life and improved motor starting
- Dampers, skewed rotors for <5% harmonic distortion
- Capacitor excitation, brushless operation

Features:

- 15 gallon steel fuel tank with fuel gauge
- Heavy duty 1 1/4"-14 gauge tubular steel cradle
- Industrial powder coat paint
- Electric start
- Full receptacle package with circuit breaker protection
- 120/240 volt receptacle for connection to a temporary power distribution system or to a building electrical service with an approved manual transfer switch for emergency/standby use
- Vibration isolation for smooth operation
- Easy to move, convenient to store
- Four-wheel dolly kit included

Accessories (optional):

- Generator cover
- Low pressure fuel solenoid kit
- 60 amp manual transfer switch kit
- Plug-in line voltage monitor
- 60 amp (NEMA 14-60P) plug

SURGE WATTS (1)	12,000
CONTINUOUS WATTS (1)	10,800
AMPS (1)	90/45
VOLTS	120/240
VOLTAGE REGULATION	+/- 5%
FREQUENCY REGULATION	+/- 3%
ENGINE BRAND	HONDA
ENGINE MODEL	GX630
ENGINE STARTER (3)	ELECTRIC
ENGINE SPEED	3600 RPM
DISPLACEMENT	688 CC
ENGINE CYLINDERS	V-TWIN
LOW OIL PROTECTION	STANDARD
dBA AT 7 METERS	78
FUEL TANK	15 GAL
FUEL USE:	GASOLINE 1.67 gal/hr NATURAL GAS 200 ft³/hr - 204,000 BTU/hr LP GAS 2.2 gal/hr - 201,304 BTU/hr
FULL PRESSURE OIL LUBE WITH SPIN-ON FILTER	INCLUDED
MOTOR STARTING (CODE G) (1) (2)	5 HP
MAIN CIRCUIT BREAKER	45A
120 VOLT RECEPTACLES	4 x NEMA 5-20R 20A
120/240 VOLT RECEPTACLES	1 x NEMA L14-30R 30A 1 x NEMA 14-60R 60A
DIMENSIONS (LxWxH)(w dolly kit)	44.7" x 36" x 33"
NET WEIGHT	425 LBS
SHIP WEIGHT	460 LBS
WARRANTY (ENG/GEN) (4)	3 YRS / 2 YRS

NOTES: (1) Based on gasoline fuel. Derate 10% for LP gas and 20% for Natural Gas. (2) Code G capacitor start motor. (3) Electric start models include battery rack and cables, battery not included. BCI Group U1, 12-volt, 300 CCA battery required. (4) Prime Power Warranty 120 days. Contact your local Honda engine service center for engine warranty assistance.

Presented by:

TRI-FUEL ← LP GASOLINE NG
HOME POWER®

Toll Free: 1-800-733-2112
sales@wincogen.com

www.wincogen.com

225 South Cordova Avenue
Le Center MN, 56057