

12kW¹ STANDBY GENERATOR



Space Saving Design

• 50% smaller than our previous 12kW generator

60% Quieter²

• Re-engineered to be 60% quieter than our previous 12kW

Designed for Easy Installation & Maintenance

- · Easy to move into installation location with two-wheel dolly
- Approved for installation as close as 18" to a building³
- Removable roof and side panels provide better service access to the engine and alternator

Symphony[®] II Power Management System

- Customizable to your home's needs
- Automatically balances the power of your home's electrical load including high wattage items like air conditioning units and electric ovens
- Offers whole house power with a more affordable home generator

BRIGGS & STRATTON® THE SMART CHOICE

For the discerning homeowner that is looking for the smartest, most reliable permanent backup power solution.



Commercial-Grade Briggs & Stratton Vanguard[™] Engine

- Powerful V-Twin OHV engine
- Easy conversion between natural gas (NG) and liquid propane vapor (LP) during installation

Quality Clean Power

• Ensures your electronics are safely powered

Corrosion Resistant Enclosure & Base

- Made with automotive grade galvanneal steel to resist rust
- Powder-coated paint for years of protection against chips and abrasions



GENERATOR SET RATINGS									
LIQUID PROPANE NATU							NATUR	RAL GAS	LIMITED WARRANTY ⁴
MODEL	VOLTAGE	PHASE	HZ	BREAKER	LP kW	LP AMPS	NG kW	NG AMPS	PARTS, LABOR, TRAVEL
Briggs & Stratton 040517	120/240	1	60	60	12	50	10.8	41.7	5 Year

and CSA (Canadian Standards Association) standard C22.2 No. 100-04 (motors and generators)

- ³ The installation manual contains specific instructions related to generator placement in addition to NFPA 37, including the requirement that carbon monoxide detectors be installed and maintained in your home.
- ⁴ Warranty details available at www.briggsandstratton.com

¹ This generator is rated in accordance with UL (Underwriters Laboratories) 2200 (stationary engine generator assemblies)

² Based on no-load sound power.





ENGINE SPECIFICATIONS						
ENG	INE	LUBRICATION				
Engine Model	Briggs & Stratton Vanguard™	Oil Capacity (oz)	48			
Engine Model Type Trim Number	389575-0002E1	Lubrication System	Full Pressure			
Engine Speed (RPM)	3600	Recommended Oil	5W30 Full Synthetic			
Engine Fuel	Liquid Propane (LP) or Natural Gas (NG)	Low Oil Pressure Sensor	Yes			
Engine Cylinder Configuration	OHV	ALTERNATOR SPECS				
Number of Cylinders	2	Manufacturer	Mecc Alte			
Displacement (cc)	38 / 627	Туре	Self-Excited, Rotation Field			
Bore & Stroke (in)	2.97 / 2.76	Voltage Regulator	Brushless			
Compression Ratio	8.3:1	Insulation	Class H			
Governor Type	Electronic	CONTROLLER FEATURES				
		Hour Meter	Yes			
Frequency Regulation	+/- 1 Hz	LED Digital Display	Yes			
Valves	OHV with Hardened Seats	Fault Code Display	Yes			
gnition System	Fixed timing Magnetron® Electric Ignition					
Starter Motor Rating Voltage	12 Volt	Weekly Exerciser	Yes			

Battery

OPERATIONS

FUEL CONSUMPTION¹ 50% Load 100% Load Liquid Propane 62.1 ft³ / hr 1.7 gal / hr 83.8 ft³ / hr 2.3 gal / hr Natural Gas 117 ft³ / hr — 172 ft³ / hr —

12 Volt

SOUND RATING AT 7 METERS

69 dBA

Lowest measurement of 12 microphones around generator. Sound level measurement at other locations around generator may be different depending upon installation configuration.

¹ Fuel consumption rates are estimated based on normal operating conditions. Generator operation may be greatly affected by elevation and the cycling operation of multiple electrical appliances – fuel flow rates may vary depending on these factors.


12kW STANDBY GENERATOR




ADDITIONAL INFORMATION						
OTHER	FEATURES	CERTIFICATION				
Enclosure Material	Galvanneal Steel with Corrosion Resistant Paint	CARB Compliant	Yes			
Overcrank Protection	Yes	NFPA Approved	Yes			
Engine Warm Up (sec)	20 or 50 Automatic Transfer Switch Controlled	cUL Listed to CSA 22.2 NO 100-04	Yes			
Engine Cool Down (min)	1	NEMA Compliant	Yes			
Response Time (sec)	26 or 56 Automatic Transfer Switch Controlled	EPA Certified Fuel System	Yes			
Monitoring Options	Basic Wireless Monitor InfoHub™ Monitor	AVAILABLE ACCESSORIES				
Continuous Battery Charging	Yes	Maintenance Kit	6035			
WEIGHT AND DIMENSIONS		Cold Weather Kit	6348			
Assembled Weight (lbs)	318	Basic Wireless Monitor	6264			
Overall Dimensions (in)	28 x 24.4 x 37.2	InfoHub	6260			
Packaged Weight (lbs)	345	Remote Status Monitor	6144			

Packaged Dimensions (in)

39 x 35.5 x 45







FUEL PIPE SIZE RECOMMENDATION CHART (CAPACITY IN THOUSANDS OF BTU/HOUR)

Natural Gas / Inlet Pressure less than 2 DSI / Pressure Dron 1/2" Water Column / Specific Gravity 0.60

	Natural Gas / Inite Pressure less than 2 PGI / Pressure Drup 1/2 Water Column / Specific Gravity 0.00						
	1/2" pipe capacity	3/4" pipe capacity	1" pipe capacity	1-1/4" pipe capacity	1-1/2" pipe capacity	2" pipe capacity	
20' Length*	118	247	466	957	1,430	2,760	
40' Length*	81	170	320	657	985	1,900	
60' Length*	65	137	257	528	791	1,520	
80' Length*	56	117	220	452	677	1,300	
100' Length*	50	104	195	400	600	1,160	

Liquid Propane / Inlet Pressure 11" Water Column / Pressure Drop 1/2" Water Column / Specific Gravity 1.50

	1/2" pipe capacity	3/4" pipe capacity	1" pipe capacity	1-1/4" pipe capacity	1-1/2" pipe capacity	2" pipe capacity
20' Length*	200	418	788	1,617	2,423	4,666
40' Length*	137	287	541	1,111	1,665	3,207
60' Length [*]	110	231	435	892	1,337	2,575
80' Length [*]	101	212	400	821	1,230	2,370
100' Length*	101	212	400	821	1,230	2,370

*Total length of piping from outlet of regulator to appliance furthest away.

ADDITIONAL INFORMATION

TRANSFER SWITCH SPECIFICATIONS					
Prewired 16 Circuit	100 AMP	Model #071076			
Standard 16 Circuit	100 AMP	Model # 071047			
Symphony [®] II	100 AMP	Model # 071071			
Symphony [®] II	150 AMP	Model # 071070			
Symphony [®] II	200 AMP	Model # 071068			
Voltage Rating	120/240				
	Select Circuit: 16				
Number of Protected Circuits -	Symphony [®] II: Whole House				
UL Approved	Yes				
NEMA 3R Rated	Yes				

SUPPORT EVERY STEP OF THE WAY

NEED HELP? Just call 800-759-2744 Our technical support team is trained to answer questions on our generators, transfer switches and accessories.

CALL TODAY FOR A FREE IN-HOME ESTIMATE! 800-743-4115

Disclaimer: Not for Prime Power or use where standby systems are legally required, for serious life safety or health hazards, or where lack of power hampers rescue of fire-fighting operations.

BRIGGS&STRATTON

POST OFFICE BOX 702 MILWAUKEE, WI 53201 USA Copyright ©2016. All rights reserved. BS1007-I – 11/16