

SUPER QUIET

SPECIFICATIONS

| | EU1000i | EU2000i / EU2000i Companion† | EU3000is | Handi EU3000i | EU6500is |
|------------------------|--|--|--|--|---|
| Engine | Honda GXH50 | Honda GX100 | Honda GX200 | Honda GX160 | Honda GX390 |
| | Single cylinder, overhead valve, air-cooled | Single cylinder, overhead cam, air-cooled | Single cylinder, overhead valve, air-cooled | Single cylinder, overhead valve, air-cooled | Single cylinder, overhead valve, air-cooled |
| Displacement | 50cc | 98.5cc | 196cc | 163cc | 389cc |
| AC output | 120V 1000W max. (8.3A) 900W rated (7.5A) | 120V 2000W max. (16.7A) 1600W rated (13.3A) | 120V 3000W max. (25A) 2800W rated (23.3A) | 120V 3000W max. (25A) 2600W rated (21.7A) | 120/240V 6500W max. (54.1/27.1A) 5500W rated (45.8/22.9A) |
| iAVR AC output | N/A | N/A | N/A | N/A | N/A |
| Receptacles | B | C / F, J† | C, F | C, F | C, F, H |
| DC output | 12V, 96W (8A) | 12V, 96W (8A) | 12V, 144W (12A) | 12V, 100W (8.3A) | N/A |
| Starting system | Recoil | Recoil | Recoil, electric | Recoil | Recoil, electric |
| Fuel tank capacity | 0.6 gal. | .95gal. | 3.4 gal. | 1.56 gal. | 4.5 gal. |
| Run time per tankful | 3.8 hrs. @ rated load, 8.3 hrs. @ 1/4 load | 4hrs. @ rated load, 9.6 hrs. @ 1/4 load | 7.2 hrs. @ rated load, 20.0 hrs. @ 1/4 load | 3.6 hrs. @ rated load, 7.7 hrs. @ 1/4 load | 4.7 hrs. @ rated load, 14.0 hrs. @ 1/4 load |
| Dimensions (L x W x H) | 17.7" x 9.4" x 15.0" | 20.1" x 11.4" x 16.7" | 25.8" x 18.9" x 22.4" | 24.5" x 14.9" x 19.3" | 33.5" x 26.4" x 27.5" |
| Noise level | 59 dB @ rated load 53 dB @ 1/4 load 86 LwA†† | 59 dB @ rated load 53 dB @ 1/4 load 89 LwA†† | 58 dB @ rated load 49 dB @ 1/4 load 90 LwA†† | 65 dB @ rated load 57 dB @ 1/4 load 91 LwA†† | 60 dB @ rated load 53 dB @ 1/4 load 91 LwA†† |
| Dry weight | 29 lbs. | 46.3 lbs. / 45.9 lbs.† | 134 lbs. | 78 lbs. | 253 lbs. |

FEATURES

| | EU1000i | EU2000i / EU2000i Companion† | EU3000is | Handi EU3000i | EU6500is |
|--|------------|---------------------------------|------------|---------------|------------|
| Honda OHV engine | • | • | • | • | • |
| Electric start/Remote start option | | | • | | • |
| Oil Alert® | • | • | • | • | • |
| Auto Throttle® | | | | | |
| Eco-Throttle™ (load dependent operation) | • | • | • | • | • |
| Electronic ignition | • | • | • | • | • |
| Simultaneous AC/DC use | • | • | • | • | • |
| Circuit breakers | Electronic | Electronic | Electronic | Electronic | Electronic |
| Fuel gauge | | | • | | • |
| i-Monitor | | | | | • |
| Wheel kit standard | | OPT | OPT | • | • |
| iAVR | | | | | |
| DAVR | | | | | |
| CycloConverter™ | | | | | |
| Inverter | • | • | • | • | • |
| One switch for engine/fuel valve on/off | • | • | | • | |
| Full tubing frame for protection | | | | | |
| USDA-qualified spark arrester/muffler | • | • | • | • | • |
| Fully enclosed for quieter operation | • | • | • | • | • |
| 120/240V selector switch | | | | | • |
| GFCI/neutral bond | | | | | |
| Residential warranty | 2 Years | 3 Years | 3 Years | 3 Years | 3 Years |
| Commercial warranty | 1 Year | 3 Years | 3 Years | 3 Years | 3 Years |

† Indicates a specification for EU2000iA Companion model only.

††LwA is an international noise level measurement that uses a weighting factor to reflect noise "tonality" in addition to the sound power (dBA) level.

Receptacle Key

| RECEPTACLE | DESCRIPTION | PLUG # | RECEPTACLE | DESCRIPTION | PLUG # |
|------------|-----------------|----------------|------------|-----------------------|--------|
| B | 15A 125V Duplex | 5-15P | D | 20A 125V GFCI Duplex | 5-20P |
| C | 20A 125V Duplex | 5-15P or 5-20P | E | 20A 125V Locking Plug | L5-20P |