



MILBANK[®]
ENERGY AT WORK

10kW GENFORCE PORTABLE GENERATOR

POWER YOU CAN DEPEND ON



V-Twin Engine – Milbank's heavy-duty V-Twin OHV engine features 680cc, a pressurized lubrication system, low oil shutdown, a shock mounted oil cooler, an automotive type oil filter and large 9.2 gallon fuel tank.

Full Cage Steel Frame – The durable, steel frame protects the generator from damage and includes a lifting kit.

GFCI-Protected Control Panel – Full GFCI-protected control panel, monitors all receptacles for ground faults

Data Center – The VFT Data Center provides volts, frequency and hours for on-site use and proper maintenance cycles.



FEATURES

- Full cage steel frame - helps to protect unit from damage
- Includes bracket kit (minor assembly required)
- Full GFCI-protected control panel, monitors all receptacles for ground faults
- VFT Data Center, provides volts, frequency and hours for on-site use and proper maintenance
- Easily converts from a bonded neutral to a floating neutral, under the alternator cover
- Bonus DC battery charger included
- Less Than 5% THD, all copper alternator
- 42 Amp main toggle, 30Amp toggle, (2) 20Amp push button
- (2) Nema 5-20R Duplex, Nema L5-30R, Nema L14-30R All with covers
- CS6369 50A Outlet
- Idle, fuel saving control - intelligent throttle control lowers to 1800 RPM when amperage demand not detected

3 YEAR WARRANTY



SPECIFICATIONS	
Model Number	MPG100001E
Starting	Electric
Rated Watts	10,000 Watts
Surge Watts	12,500 Watts
Run Time @ 1/2 Load	11 Hours
Engine	OHV, 4-Stroke
Engine Displacement	680cc V-Twin
Warranty	3 years
EPA Compliant	Yes
CARB Compliant	Yes
Fuel Tank Capacity	9.2 Gallons
Low Oil Shutdown	Yes
Automatic Fuel Shut-Off	Yes
Excitation	Brush
Unit Dimensions L x W x H (inches)	30.7 x 31.1 x 31.3
Unit Weight	300 lbs
Carton Dimensions L x W x H (inches)	34.6 x 27.5 x 33.2
Shipping Weight	310 lbs
Outlets (Quantity) NEMA 5-20R (125VAC 20A Duplex)	2
20 Amp push button circuit breakers	2
NEMA L14-30R (125/250VAC 30A Twist Lock)	1
2 Pole Toggle-Type Main Line Breaker	30 Amps
NEMA L5-30R (Twist Lock)	1
NEMA 50A (Twist Lock)	1
Oil Bottle (One bottle sized for engine: SAE10W30)	Yes
12V DC Outlet	Yes
Oil Funnel	Yes
Multi-Outlet 25' Power Cord	No
Battery	Yes
Wheel Kit	Yes
Tool Kit	Yes
Fuel Gauge	Yes
Hour Meter	Yes
Power Cord (25'; 30 AMPs; rated up to 300 Volts)	Yes (sold separately)