

Dependable jobsite power.



## **FEATURES**

- Brushless alternator design Low maintenance for years of dependable service.
- **Superior voltage regulation** Helps to keep tools and equipment running at optimal levels and last longer.
- Control panel Rugged design withstands rough handling on jobsites or in the back of a truck.
- Full-panel GFCI protection OSHA and NEC compliant.
- Hour Meter Allows accurate tracking of usage and maintenance intervals. Standard on 3.6 kW and 6kW models.
- **Automatic idle control** Reduces engine speed during periods of no load and improves fuel economy.
- Industrial grade engines GA-Series generators are powered with Honda GX series engines and feature low oil shutdown on all models.
- **Electric start** Available on GA6HRS and GA97HEA.
- Warranty All GA-Series generators are covered by a two-year parts and labor warranty.

#### Voltmeter

This feature serves as a convenient diagnostic tool on the jobsite. The operator can quickly tell whether or not the generator is producing the correct voltage and prevent overheating of expensive tools and equipment.



#### **Silent Type Muffler**

Reduces noise level on Honda units. USFS-approved spark arrestors standard on 2.5kW through 6kW Honda-powered models.

#### Reliability

GA-Series generators use a brushless design that minimizes maintenance by eliminating the carbon brushes and slip rings common on competitive models.



### GA6HR 6000 watts max.

Honda engine, recoil start Features available on all models except where noted.



# There's a size and model for every application.



GA25HR 2500 watts max.

Honda engine, recoil start



GA36HR 3600 watts max.

Honda engine, recoil start



GA6HRS 6000 watts max.

Honda engine, recoil/electric start

Battery sold separately



#### GA97HEA 9700 watts max.

Honda engine, electric start

Battery sold separately



Optional wheel kit (WKT97) is available for GA97HEA generator.



# **Portable Generator Specifications**

| MODEL                        | GA25HR               | GA36HR    | GA6HR     | GA6HRS                | GA97HEA     |
|------------------------------|----------------------|-----------|-----------|-----------------------|-------------|
| Alternator Design            | Brushless            |           |           |                       |             |
| Maximum Watts                | 2,500                | 3,600     | 6,000     | 6,000                 | 9,700       |
| Continuous Watts             | 2,200                | 3,200     | 5,000     | 5,000                 | 8,400       |
| Voltage                      | 120V                 | 120/240V  |           |                       |             |
| Max. Amp @ 120V              | 20.8                 | 30        | 50        | 50                    | 80.8        |
| Cont. Amp @ 120V             | 18.3                 | 26.6      | 41.6      | 41.6                  | 70          |
| Max. Amp @ 240V              | N/A                  | 15        | 25        | 25                    | 40.4        |
| Cont. Amp @240V              | N/A                  | 13.3      | 20.8      | 20.8                  | 35          |
| Frequency/Phase              | 60 Hz / Single phase |           |           |                       |             |
| Voltmeter                    | Standard             |           |           |                       | _           |
| Full Power Switch            | N/A                  | Standard  |           |                       | N/A         |
| RECEPTACLES                  |                      |           |           |                       |             |
| 5-20R 125V GFCI 20A          | 3                    | 3 (2)     | 3 (2)     | 3(2)                  | 3(2)        |
| L5-20R 125V; T-Lock 20A      | 3                    | 3         | 3         | 3                     |             |
| L5-30R 125V; T-Lock 30A      |                      | 3         | 3         | 3                     | 3           |
| L6-20R 250V; T-Lock 20A      |                      |           |           |                       | 3           |
| L14-20R 125/250V; T-Lock 20A |                      | 3         |           |                       |             |
| L14-30R 125/250V; T-Lock 30A |                      |           | 3         | 3                     | 3           |
| ENGINE SPECIFICATIONS        |                      |           |           |                       |             |
| Manufacturer                 | Honda                | Honda     | Honda     | Honda                 | Honda       |
| Model                        | GX-160               | GX-240    | GX-340    | GX-340                | GX-630      |
| Horsepower (KW)‡‡            | 4.8 (4.1)            | 7.1 (5.3) | 9.5 (7.1) | 9.5 (7.1)             | 20.8 (15.5) |
| Rated Speed — RPM            | 3,600                |           |           |                       |             |
| Low Oil Shutdown             | Standard             |           |           |                       |             |
| Starting Systems*            | Recoil               |           |           | Recoil with Electric* | Electric*   |
| Battery Spec                 | N/A                  |           |           | 12N24-3A              | SP-30       |
| Fuel Capacity — gal (ltr)    | 3.2 (12)             | 5.0 (19)  | 5.0 (19)  | 5.0 (19)              | 10.0 (37.8) |
| Running Time — hr./tank**    | 8.9                  | 9.0       | 5.7       | 5.7                   | 8           |
| Fuel Gauge                   | Standard             |           |           |                       |             |
| Hour Meter                   | Standard             |           |           | N/A                   |             |
| Automatic Idle Control       | N/A Standard         |           |           | ndard                 |             |
| Sound Level dB@ 23 ft.       | 70                   | 76        | 75        | 75                    | 79          |
| DIMENSIONS AND WEIGHT        |                      |           |           |                       |             |
| Length — in. (cm)            | 21 (53)              | 24½ (62)  | 25½ (65)  | 25½ (65)              | 31½ (80)    |
| Width — in. (cm)             | 17¾ (45)             | 22(56)    | 22 (56)   | 22½ (57)              | 21¼ (54)    |
| Height — in. (cm)            | 20 (51)              | 21¼ (54)  | 21¼ (54)  | 21¼ (54)              | 27½ (70)    |
| Dry Weight — Ibs. (kg)       | 110 (50)             | 196 (89)  | 221 (100) | 241 (109)             | 342 (155)   |
| OPTIONS                      |                      |           |           |                       |             |
| Wheel Kit                    | UWKB                 |           | Standard  |                       | WKT-97      |

<sup>‡‡</sup> Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. Multiquip Inc. and its subsidiary companies makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy of the engine power rating. Users are advised to consult the engine manufacturer's owners manual and its website for specific information regarding the engine power rating.

Note: Some units may be shown with optional equipment.

Your Multiquip dealer is:

Connect with us on









<sup>\*</sup> GA6HRS/GA97HEA is shipped less battery.

<sup>\*\*</sup> All running times computed at full load using fuel consumption rates supplied by engine manufaturer.