

# SGX Series SPECIFICATIONS



	SGX3500	SGX5000	SGX7500E
Emission Compliancy	50 state	50 state	50 state
CSA Compliant	Yes	Yes	Yes
Type	Brush Type	Brush Type	Brush Type
Voltage Regulation	AVR	AVR	AVR
Frequency	60HZ/Single	60HZ/Single	60HZ/Single
Voltage	120/240	120/240	120/240
Max Output (watts)	3500	4900	7300
Max Amps	29.2/14.6	40.8/20.4	60.8/30.4
Rated Output (watts)	3200	4500	6700
Rated Amps	26.6/13.3	37.5/18.8	55.8/27.9
dba @ rated output (7 meters)	72	76	76
Current Protection	Dual Pole Magnetic Circuit Breaker & GFCI	Dual Pole Magnetic Circuit Breaker & GFCI	Dual Pole Magnetic & Thermal Circuit Breakers & GFCI
Model	EX21 7 HP	EX30 9.5 HP	EX40 14 HP
Type	Subaru OHC	Subaru OHC	Subaru OHC
Low Oil System	Low Oil Shutdown	Low Oil Shutdown	Low Oil Shutdown
Fuel Tank Capacity	4 gallons	8 gallons	8 gallons
Hours at rated load	8 hours	10.7 hours	7 hours
Hours at rated 1/2 load	10.8 hours	14.6 hours	10.4 hours
Starting System	Recoil	Recoil	Electric with Recoil Backup
Battery Included - Battery replacement or equal	N/A	N/A	Sealed 12V 18 AHr. Interstate BSL1116
Dimensions (LxWxH)*	28"x25"x26"	30"x29"x29"	30"x29"x29"
Dimensions less wheel kit (LxWxH)	24"x17"x21"	28"x21"x24"	28"x21"x24"
Dry Weight (includes wheel kit)	137 lbs.	177 lbs.	229 lbs.
GFCI 120V, 20A Duplex	2	2	2
120V, 30A Twist lock	N/A	1	1
120/240V, 30A Twist lock	1	1	1
Hourmeter	Yes	Yes	Yes
Wheel Kit	Yes	Yes	Yes

Specifications subject to change without notice | \*Dimensions include mounted wheel kit (less extended handles)

PUB-GENSGX rev. 12/2014



905 Telser Road  
Lake Zurich, IL 60047, USA  
tel: 847-540-7300 | toll free: 800-277-6246  
email: sales@subarupower.com  
web: www.subarupower.com

Using a generator indoors can kill you in minutes!  
Generator exhaust contains carbon monoxide. This is a poison you cannot see or smell. Never use inside a home or garage, even if doors and windows are open. Only use outside and far away from window, doors and vents.