



# Tillotson®

## POWER PRODUCTS

### All generators feature:

- Heavy-duty Drop Handles
- Extra Large Run-Flat Wheels
- Square Tubular Steel to reduce vibration
- Run Time Meter
- Low Oil Automatic Shut Off
- 2000+ hour modified racing engine

#### TPP-4500G-A



- 4500W Peak/3500W Rated
- Remote electric start (Lets you start the generator from up to 300' away) with electric key and recoil options
- 5 Covered Outlets:
  - 2 Standard GFCI outlet
  - 1 120V/30 Amp twist lock outlet
  - 1 120V/30 Amp RV outlet
  - 1 12V/8.3 Amp outlet
- 11 hour Run time at half load
- 72db
- Compatible with TillotsonTCT carburetor for lower noise, lower emissions, better fuel economy
- EPA and CARB certified

#### TPP-4500DF-A



- 4500W Peak/3500W Rated
- Dual-Fuel operation (gasoline and liquid propane)
- Electric start with recoil option
- 5 Covered Outlets:
  - 2 Standard GFCI outlet
  - 1 120v/30 Amp twist lock outlet
  - 1 120V/30 Amp RV outlet
  - 1 12V/8.3 Amp outlet
- 11 hour Run time at half load
- 72db
- Compatible with TillotsonTCT carburetor for lower noise, lower emissions, better fuel economy
- EPA Certified (not available in California)

**TPP-7500G-A**



- 7500W Peak/6000W Rated
- Remote electric start (Lets you start the generator from up to 300' away) with electric key and recoil options
- 7 Covered Outlets:
  - 4 Standard GFCI outlet
  - 1 120V/30 Amp twist lock outlet
  - 1 120V/240V twist lock outlet
  - 1 12V/8.3 Amp outlet
- 12 hour Run time at half load
- 75 db
- EPA and CARB certified

**TPP-7500G-A**



- 7500W Peak/6000W Rated
- Dual-Fuel operation (gasoline and liquid propane)
- Electric start with recoil option
- 7 Covered Outlets:
  - 4 Standard GFCI outlet
  - 1 120V/30 Amp twist lock outlet
  - 1 120V/240V twist lock outlet
  - 1 12V/8.3 Amp outlet
- 12 hour Run time at half load
- 75 db
- EPA Certified (not available in California)

**TPP-10000G-A**



- 10000W Peak/7500W Rated
- Remote electric start (Lets you start the generator from up to 300' away) with electric key and recoil options
- 8 Covered Outlets:
  - 4 Standard GFCI outlet
  - 1 120V/30 Amp twist lock outlet
  - 1 120V/50 Amp twist lock outlet
  - 1 120V/240V twist lock outlet
  - 1 12V/8.3 Amp outlet
- 10.5 hour Run time at half load
- 76 db
- EPA and CARB Certified