

# WINCO®

Quality Generators Since 1927

## W6010DE

**YANMAR**



### Engine:

- YANMAR L100V
- EPA Tier IV
- Cast iron sleeves
- Commercial grade engine
- Single-cylinder, air cooled direct injection engine utilizes a counter-balancing system for smooth, high speed operation
- 12V electric start with recoil assist
- 435cc, 3600 RPM, natural aspiration

### Generator End:

- Made in the USA
- 100% copper windings - longer life and improved motor starting
- 100% load tested (Not statistically sampled)
- Switchless full power allows the full rated output from a single outlet without switching voltage settings

### Components:

- 7 gallon steel fuel tank
- Powder coat paint on all steel for an incredibly durable finish
- NEMA 5-20R receptacles have GFCI protection with a metal cover to protect against the elements
- NEMA 14-30R receptacle with GFCI protection
- Hour meter
- Standard lifting eye

Presented by:

SURGE WATTS	6000
CONTINUOUS WATTS	5500
AMPS	45.8 / 22.9
VOLTS	120/240
VOLTAGE REGULATION	+/-5%
FREQUENCY REGULATION	+/-3%
ENGINE BRAND	YANMAR
ENGINE MODEL	L100V
ENGINE STARTER	ELECTRIC
ENGINE SPEED	3600 RPM
DISPLACEMENT	435 CC
ENGINE CYLINDERS	SINGLE
LOW OIL PROTECTION	STANDARD/PRESSURE
dBA AT 7 METERS	78
FUEL TANK	7 GAL
FULL LOAD RUN TIME	12.2 HRS
FUEL USE (GAL/HR)	.57
OIL STRAINER/ MOUNTED IN ENGINE	STANDARD
MOTOR STARTING (CODE G)	2 HP
MAIN CIRCUIT BREAKER	45 AMP, 120V / 25 AMP, 240V
HOUR METER	STANDARD
120 VOLT RECEPTACLES	(2) NEMA 5-20R (GFCI) (1) NEMA 5-50R 50AMP
120/240 VOLT RECEPTACLE	(1) NEMA L14-30R 30 AMP (GFCI)
DIMENSIONS (LxWxH)	33.75" x 23" x 22.25"
SHIPPING DIMENSIONS	35" x 24" x 28"
NET WEIGHT	308 LBS
SHIP WEIGHT	326 LBS
WARRANTY (ENG/GEN)	2 YR, 2000 HRS / 2 YRS

Toll Free: 1-800-733-2112  
sales@wincogen.com

[www.wincogen.com](http://www.wincogen.com)

225 South Cordova Avenue  
Le Center MN, 56057