



Model #	100103	100109	100110	100111
Running Watts	3800	6500	9200	12,000
Starting Watts	4750	8125	11,000	15,000
Engine	224cc OHV	389cc OHV	459cc OHV	720cc V-twin
Start Type	Recoil	Recoil	Electric	Electric
Outlets	L5-30R, TT-30, (2) 5-20R	L14-30R, (4) 5-20R GFCI	(4) 5-20R GFCI, L14-30R, 14-50R	(4) 5-20R GFCI, L5-30R, L14-30R, 14-50R
Intelligauge	WITH POWER METER			Yes
Low Oil Shut-off	Yes			
Fuel Tank (Gal)	3.4	7.7		11
Run Time <sup>50% Load</sup>	8 hours	11 hours	9 hours	
Wheels/Handle	8 in. Never Flat / Single	9.5 in. Never Flat / U-Shaped		12 in. Never Flat / U-Shaped
Frame	1 in. Steel	1.375 in. Steel		
Weight <sup>Net/Gross</sup>	106.9 / 119 lb.	173.7 / 185.2 lb.	205.5 / 218.5 lb.	TBD
Dimensions <sup>L x W x H</sup>	26.3 x 23.7 x 22.5 in.	27.6 x 27.6 x 26.6 in.	27.7 x 27.6 x 26.6 in.	TBD
Package <sup>L x W x H</sup>	28.2 X 18.7 X 20.5 in.	32.1 X 21.9 X 24.4 in.	32.5 x 21.9 x 24.4 in.	TBD
120/240 Volt Operation	120	120/240		
Emissions Certification	EPA / CARB (50 State)			
Battery	N/A	12V DC 15Ah		12V DC 33Ah
Warranty	2 Year Limited (2 Years Parts & Labor) (180 Days Commercial)			