

8125
STARTING WATTS

6500
RUNNING WATTS

SPECIFICATIONS

Starting Type	Electric, Recoil
Outlets (full panel GFCI)	(1) 120/240V 27.1A L14-30R Twist Lock (1) 120V 27.1A L5-30R Twist Lock (2) 120V 20A 5-20R Duplex
Voltmeter Type	5-mode Intelligauge + CO Shield
Volts (V)	120/240
Total Harmonic Distortion	<5%
Noise Level (dBA)	74
Run Time (h. @ ½ load)	12.5
Engine Size (cc)	389
Fuel Type(s)	Gasoline
Gasoline Capacity (gal.)	8.5
Oil Type	10W-30
Oil Capacity (fl. oz.)	37.2
Low Oil Shut-off	Yes
Emissions	EPA/CARB



CONTROLS and FEATURES

- EXTREME-DUTY CAGE**
Steel frame protects generator in rough environments
- STEEL LIFT HOOK**
Easily transport by crane or forklift
- IDLE CONTROL**
Saves fuel and reduces noise
- FULL PANEL GFCI**
OSHA worksite compliant
- COMMERCIAL ENGINE**
Long lasting Champion engine
- LOCKING HANDLE**
Easily move and store
- INTELLIGAUGE**
5-mode digital display shows operating info and stats
- VOLT GUARD**
Stops power surges
- CO SHIELD**
Carbon monoxide auto-shutoff system
- COLD START**
No hassle in cold weather
- LOW THD**
Provides clean power for sensitive items



PACKAGE (gross)
Weight: 232 lb.
Size: 34.4 x 21.9 x 25.7 in.



PRODUCT (net)
Weight: 220 lb.
Size: 32.4 x 27.8 x 31.5 in.