

2018 EPA Exhaust Emission Compliance Statement C60 N6 Standby

60 Hz Spark Ignited Generator Set

Compliance Information:

The engine used in this generator set complies with U.S. EPA emissions regulations under the provisions of 40 CFR Part 60, Stationary Emergency Spark-Ignited emissions limits when tested on 6 mode cycle pf Part 90.

Cummins Inc.
JCEXB05.9ARB-004
8/25/2017
8/25/2017
JCEXB05.9ARB

Engine Information:

Model:	QSJ5.9G-G2
Engine Nameplate HP:	100.3
Туре:	4 Cycle, In-Line, 6 Cylinder
Aspiration:	Naturally Aspirated
Emission Control Device:	Electronic Air/Fuel Ratio Control and Closed-Loop Breather System

Bore:	4.02 in. (102 mm)
Stroke:	4.72 in. (120 mm)
Displacement:	359.0 cu. in. (6 liters)
Compression Ratio:	8.5:1
Exhaust Stack Diameter:	4.0 in (102 mm)

U.S. Environmental Protection Agency Station Emergency SI Emission Limits							
	Grams per BHP-hr		Grams pe	e <mark>r kW</mark> m-hr			
Natural Gas	NOx NMHC	<u>co</u>	<u>NOx</u> <u>NMHC</u>	<u>C0</u>			
Test Results	4.8	66	6.4	88.5			
EPA Emissions Limit	10.0	387	13.4	519			

	Grams per BHP-hr		Grams pe	er kWm-hr
Propane (LP)	<u>NOx</u> NMHC	<u>co</u>	<u>NOx</u> NMHC	<u>co</u>
Test Results	6.9	84.5	9.3	113.3
EPA Emissions Limit	10.0	387	13.4	519

Tests conducted using alternate methods, instrumentation, fuel or reference conditions can yield different results.

Engine operation with excessive air intake or exhaust restriction beyond published maximum limits, or with improper maintenance, may result in elevated emission levels.