

EP2500X	EG4000CL	EG5000CL	EG6500CL
Honda GX160	Honda GX270	Honda GX390	Honda GX390
Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled
160cc	270cc	389cc	389cc
120V 2500W max. (20.8A) 2300W rated (19.2A)	120/240V 4000W max. (33.3/16.7A) 3500W rated (29.2/14.6A)	120/240V 5000W max. (41.2/20.8A) 4500W rated (37.5/18.6A)	120/240V 6500W max. (54.2/27.1A) 5500W rated (45.8/22.9A)
N/A	N/A	N/A	N/A
C	C, F, G	C, F, H	C, F, H
N/A	N/A	N/A	N/A
Recoil	Recoil	Recoil	Recoil
3.83 gal.	6.3 gal.	6.3 gal.	6.3 gal.
10.2 hrs. @ rated load, 15.3 hrs. @ 1/2 load	15.7 hrs. @ 1/2 load	11 hrs. @ 1/2 load	10 hrs. @ 1/2 load
23.5" x 17.1" x 17.2"	26.8" x 22.8" x 22.5"	26.8" x 22.8" x 22.6"	26.8" x 22.8" x 22.7"
69 dB @ rated load 96 LwA ^{††}	72 dB @ rated load 97 LwA ^{††}	73 dB @ rated load 100 LwA ^{††}	74 dB @ rated load 101 LwA ^{††}
99 lbs.	155 lbs.	177 lbs.	182 lbs.
EP2500X	EG4000CL	EG5000CL	EG6500CL
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
OPT	OPT	OPT	OPT
	•	•	•
•	•	•	•
•	•	•	•
	•	•	•
3 Years	3 Years	3 Years	3 Years
3 Years	3 Years	3 Years	3 Years

SPECIFICATIONS

Engine

Displacement

AC output

iAVR AC output

Receptacles

DC output

Starting system

Fuel tank capacity

Run time per tankful

Dimensions (L x W x H)

Noise level

Dry weight

FEATURES

Honda OHV engine

Electric start/Remote start option

Oil Alert®

Auto Throttle®

Eco-Throttle™ (load dependent operation)

Electronic ignition

Simultaneous AC/DC use

Circuit breakers

Fuel gauge

i-Monitor

Wheel kit standard

iAVR

DAVR

CycloConverter™

Inverter

One switch for engine/fuel valve on/off

Full tubing frame for protection

USDA-qualified spark arrester/muffler

Fully enclosed for quieter operation

120/240V selector switch

GFCI/neutral bond

Residential warranty

Commercial warranty

RECEPTACLE	DESCRIPTION	PLUG #
F	30A 125V Locking Plug	L5-30P
G	20A 125/250V Locking Plug	L14-20P

RECEPTACLE	DESCRIPTION	PLUG #
H	30A 125/250V Locking Plug	L14-30P
I	50A 125/250V Locking Plug	CS6365

** with hanger