

# SUPER QUIET

## SPECIFICATIONS

	EU1000iA2	EU2000iA / EU2000iA Companion†	EU3000iS	Handi EU3000i	EU6500iSA
Engine	Honda GXH50	Honda GX100	Honda GX200	Honda GX160	Honda GX390
	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead cam, air-cooled	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled
Displacement	50cc	98.5cc	196cc	163cc	389cc
AC output	120V 1000W max. (8.3A) 900W rated (7.5A)	120V 2000W max. (16.7A) 1600W rated (13.3A)	120V 3000W max. (25A) 2800W rated (23.3A)	120V 3000W max. (25A) 2600W rated (21.7A)	120/240V 6500W max. (54.1/27.1A) 5500W rated (45.8/22.9A)
iAVR AC output	N/A	N/A	N/A	N/A	N/A
Receptacles	B	C / F, J†	C, F	C, F	C, F, H
DC output	12V, 96W (8A)	12V, 96W (8A)	12V, 144W (12A)	12V, 100W (8.3A)	N/A
Starting system	Recoil	Recoil	Recoil, electric	Recoil	Recoil, electric
Fuel tank capacity	0.6 gal.	1.1 gal. / .95gal.†	3.4 gal.	1.56 gal.	4.5 gal.
Run time per tankful	3.8 hrs. @ rated load, 8.3 hrs. @ 1/4 load	4hrs. @ rated load, 9.6 hrs. @ 1/4 load	7.2 hrs. @ rated load, 20.0 hrs. @ 1/4 load	3.6 hrs. @ rated load, 7.7 hrs. @ 1/4 load	4.7 hrs. @ rated load, 14.0 hrs. @ 1/4 load
Dimensions (L x W x H)	17.7" x 9.4" x 15.0"	20.1" x 11.4" x 16.7"	25.8" x 18.9" x 22.4"	24.5" x 14.9" x 19.3"	33.5" x 26.4" x 27.5"
Noise level	59 dB @ rated load 53 dB @ 1/4 load 86 LwA††	59 dB @ rated load 53 dB @ 1/4 load 89 LwA††	58 dB @ rated load 49 dB @ 1/4 load 90 LwA††	65 dB @ rated load 57 dB @ 1/4 load 91 LwA††	60 dB @ rated load 53 dB @ 1/4 load 91 LwA††
Dry weight	29 lbs.	46.3 lbs. / 45.9 lbs.†	134 lbs.	78 lbs.	253 lbs.

## FEATURES

	EU1000iA2	EU2000iA / EU2000iA Companion†	EU3000iS	Handi EU3000i	EU6500iSA
Honda OHV engine	•	•	•	•	•
Electric start/Remote start option					•
Oil Alert®	•	•	•	•	•
Auto Throttle®					
Eco-Throttle™ (load dependent operation)	•	•	•	•	•
Electronic ignition	•	•	•	•	•
Simultaneous AC/DC use	•	•	•	•	
Circuit breakers	Electronic	Electronic	Electronic	Electronic	Electronic
Fuel gauge			•	•	•
i-Monitor					•
Wheel kit standard		OPT	OPT	•	•
iAVR					
DAVR					
CycloConverter™					
Inverter	•	•	•	•	•
One switch for engine/fuel valve on/off	•	•		•	
Full tubing frame for protection					
USDA-qualified spark arrester/muffler	•	•	•	•	•
Fully enclosed for quieter operation	•	•	•	•	•
120/240V selector switch					•
GFCI/neutral bond					
Residential warranty	2 Years	3 Years	3 Years	3 Years	3 Years
Commercial warranty	1 Year	3 Years	3 Years	3 Years	3 Years

† Indicates a specification for EU2000iA Companion model only.  
††LwA is an international noise level measurement that uses a weighting factor to reflect noise "tonality" in addition to the sound power (dBA) level.

Receptacle Key

RECEPTACLE	DESCRIPTION	PLUG #	RECEPTACLE	DESCRIPTION	PLUG #
B	15A 125V Duplex	5-15P	D	20A 125V GFCI Duplex	5-20P
C	20A 125V Duplex	5-15P or 5-20P	E	20A 125V Locking Plug	L5-20P