## Residential/Light Commercial Generator Accessories

# **KOHLER**. Power Systems

**Battery Heater Kits** 





Battery Heater Kit with Wrap and Pad, Typical



Battery Heater Kit with Wrap, Typical

#### **Applicable Models**

- 8.5/12/17/18RES/RESL
- 8/10/12RESV/RESVL
- 14/20RES/RESL
- 14/20RESA/RESAL, 120 Volts
- 14/20RESA, 240 Volts
- 15/30RES/RESA
- 15/30RYG/REYG
- 20RESB

- 20RESC/RESCL, 120 Volts
- 20RESC, 240 Volts
- 20RESD
- 24/30RCL
- 38/48/60RCL
- 38RCLB
- 48RCLA
- 40-150ERES (includes ERESB, ERESC, and ERESD)

#### **Description**

The battery heater kit includes a battery heating wrap to help increase the battery temperature in cold climates. Some kits also include a heating pad to install under the battery. The battery heaters are connected to a thermostat for controlled heating. When temperatures fall below  $18^{\circ}$ C ( $65^{\circ}$ F), the thermostat activates the battery heaters, maintaining optimum battery temperature. The thermostat turns the heater off at  $27^{\circ}$ C ( $80^{\circ}$ F).

Battery heater kits are recommended for generators installed in regions where the temperature regularly falls below  $0^{\circ}$ C (32°F).

KOHLER CO., Kohler, Wisconsin 53044 USA Phone 920-457-4441, Fax 920-459-1646 For the nearest sales and service outlet in the US and Canada, phone 1-800-544-2444 KOHLERPower.com Kohler Power Systems Asia Pacific Headquarters 7 Jurong Pier Road Singapore 619159 Phone (65) 6264-6422, Fax (65) 6264-6455

### **Specifications**

Kit Numbers	GM79481-KP1	PA-352359	GM89021-KP1	GM89022-KP1	GM92406-KP2-QS	GM92406-KP3-QS
Models	24/30RCL 38/48/60RCL 38RCLB 48RCLA	40-150ERES (B,C,D)	14/20RES(L) 20RESB 20RESD	8.5/12RES(L) 15/30RES/RESA 15/30RYG/REYG 17/18RES(L)	14/20RESA 20RESC (240 Volts)	8/10/12RESV(L) 14/20RESA(L) 20RESC(L) (120 Volts)
Volts	120	120	120	120	240	120
Heater pad rating, Watts	_	30	30	31	_	_
Heater wrap rating, Watts	80				50	
Thermostat on temperature	18°C (65°F)				18°C (65°F)	
Thermostat off temperature	27°C (80°F)				27°C (80°F)	
Battery wrap length, mm (in.)	1118 (44)				711 (28)	
Power cord length, mm (in.)	1676 (66)				1829 (72)	

DISTRIBUTED BY
----------------

Availability is subject to change without notice. Kohler Co. reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever. Contact your local Kohler® generator distributor for availability.

© 2013, 2014, 2015, 2016 by Kohler Co. All rights reserved.