

## PTO GENERATORS – 3600RPM

		
	PTO15/12	PTO30/25M
<b>Voltage</b>	120/240 Vac	120/240 Vac
<b>Max. output</b>	15,000 W	30,000 W
<b>Rated output</b>	12,000 W	25,000 W
<b>Rated current</b>	100 A @ 120 V 50 A @ 240 V	208 A @ 120 V 104 A @ 240 V
<b>Frequency</b>	60 Hz	60 Hz
<b>Generator RPM</b>	3600	3600
<b>Tractor PTO RPM</b>	540	540
<b>Generator shaft</b>	1 $\frac{3}{8}$ in 6-spline	1 $\frac{3}{8}$ in 6-spline
<b>Required PTO power</b>	25 hp	50 hp
<b>Max. motor starting code G</b>	7.5	10
<b>Receptacles</b>	One 120Vac 20A duplex One 240Vac 30A locking One 240Vac 50A straight-blade	One 120Vac 20A duplex One 240Vac 30A locking One 240Vac full-power connector
<b>Dimensions, L x W x H</b>	29 x 11 x 16 in (74 x 28 x 41 cm)	29 x 13 $\frac{3}{4}$ x 21 in (74 x 35 x 53 cm)
<b>Dry weight, approx.</b>	159 lb (72 kg)	303 lb (137 kg)
<b>Optional accessories</b>	Drive shaft, 37–50 in (94–127 cm) Drive shaft, 64–79 in (163–200 cm) 2-wheel trailer 3-point hitch platform	Drive shaft, 37–50 in (94–127 cm) Drive shaft, 64–79 in (163–200 cm) 2-wheel trailer 3-point hitch platform
<p><b>Deratings:</b> Ratings apply for altitudes from sea level up to 1,000 feet (305 meters) with typical cooling, normal ambient temperature and gasoline fuel. Reduce ratings 3.5% for each 1000 feet (305 meters) above sea level and 1.0% for each 10°F rise above 60°F (5.6°C above 15.6°C).</p>		