

材料安全数据表 Material Safety Data Sheet

报告编号Report No.: SA2009472M 01002

样品名称: 便携式储能电源

Sample Name: Portable power station

样品型号:

Model: iGen600s

委托单位: 恒科能源(广东)有限公司

Applicant: Hengke Energy (GuangDong) Co., Ltd

签发日期:

2020-10-13 Issue Date:



第一部分 产品和厂商信息 Section 1 Identification of the product and supplier		
样品名称	便携式储能电源	
Sample Name	Protable power station	
样品型号 Model Name	iGen600s	
规格 Rating	19V (Internal battery 14.8V) 40000mAh 592Wh	
测试实验室	东莞市安磁检测技术有限公司	
Testing laboratory	Dongguan Anci Electronic Technology Co., Ltd.	
测试地址	广东东莞市松山湖高新技术产业开发区总部2路11号A座1-2层	
Testing Address	1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan Lake Hitech Industrial, Development Zone, Dongguan City, Guangdong Pr. China	
委托单位	恒科能源(广东)有限公司	
Applicant	Hengke Energy (GuangDong) Co., Ltd	
委托单位地址	广东省东莞市樟木头金岭路17号	
Applicant Address	No.17, JinlingRoad, Zhangmutou, Dongguan, Guangdong Province	
生产单位Manufacturer	恒科能源(广东)有限公司 Hengke Energy (GuangDong) Co., Ltd	
生产单位地址	广东省东莞市樟木头金岭路17号	
Manufacturer Address	No.17, JinlingRoad, Zhangmutou, Dongguan, Guangdong Province	
鉴定依据	依据GB/T16483-2008&ISO11014:2009编制	
Inspection according to	According to GB/T16483-2008&ISO11014:2009	
紧急联系电话 Emergency telephone call	+86-769-893886595	
测试日期 Tested date	2020-09-25 to 2020-10-12	

检测 Tested by

防,保承

审核 Reviewed by ANCI SO ANCI S

第二部分 成分/组成信息 Section 2 Composition/Information on Ingredient				
危险成分(化学名称) Hazardous Ingredients (Chemical Name)	含量及含量百分比(%) Concentration or concentration ranges (%)	CAS编号 CAS Number		
镍钴锰酸锂 Lithium Nickel Cobalt Manganese Oxide	49.5	182442-95-1		
聚偏氟乙烯 PVDF	0.33	24937-79-9		
铝 Aluminium	7.6	7429-90-5		
石墨 Graphite	16.3	7782-42-5		
丁苯橡胶 SBR	0.05	61789-96-6		
羧甲基纤维素 Carboxymethylcellulose	0.28	9000-11-7		
铜 Copper	6.96	7440-50-8		
镍 Nickel	0.06	7440-02-0		
六氟磷酸锂 Lithium Hexaflourophosphate	10.96	21324-40-3		
聚乙烯 Polyethlene	4.03	9002-88-4		
尼龙 Nylon	3.93	24937-16-4		

第三部分 主要危险性鉴定 Section 3 Hazards Identification		
爆炸危险性	该物品不属于爆炸危险品	
Explosive risk	This article does not belong to the explosion dangerous goods	
易燃危险性	该物品不属于易燃危险品	
Flammable risk	This article does not belong to the flammable material	
氧化危险性	该物品不属于氧化危险品	
Oxidation risk	This article does not belong to the oxidation of dangerous goods	
毒害危险性	该物品不属于毒害危险品	
Toxic risk	This article does not belong to the toxic dangerous goods	
放射危险性	该物品不属于放射危险品	
Radioactive risk	This article does not belong to the radiation of dangerous goods	
腐蚀危险性	该物品不属于腐蚀危险品	
Mordant risk	This article does not belong to the corrosion of dangerous goods	
其他危险性	该物品为便携式储能电源,瓦时率为592Wh。	
other risk	This article is the Portable power station, Watt hour rate 592Wh.	

第四部分 急救措施 Section 4 First aid measures

眼睛接触: 提起眼皮用大量水冲洗眼睛至少15分钟, 立即就医。

After Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

皮肤接触:脱掉被污染的衣服,并用大量水或淋浴冲洗皮肤15分钟,立即就医。

After Skin Contact: Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.

吸入: 如有吸入,迅速脱离现场至新鲜空气处,如果停止呼吸,进行人工呼吸。如果呼吸困难,供给氧气。

After Inhalation: If inhaled, quickly leave the site to fresh air. If you stop breathing, perform artificial respiration. If breathing is difficult, supply oxygen.

食入: 如有知觉,请用水冲洗口腔,就医。

After Ingestion: If swallowed, wash out mouth with water provided person is conscious .Call a physician.

第五部分 消防措施

Section 5 Fire-fighting measures

危险特性: 在火灾时可释放有害浓烟、气体或者蒸汽。

Characteristics of Hazard: Toxic fumes; gases or vapors may evolve on burning.

有害燃烧产物:一氧化碳和二氧化碳、HF、氟磷化物

Hazardous Combustion Products: CO,CO2, HF, phosphorus fluoride.

灭火方法及灭火剂:对锂电池,大量冷水是一个有效的灭火剂。不要使用温或热水。不要使用哈龙类灭火材料。

可使用干粉、沙、土。

Fire-extinguishing Methods and Extinguishing Media: Copious amounts of cold water are an effective extinguishing medium for lithium batteries. Don't use warm or hot water. Don't use Halon type extinguishing material.

May use dry powder, sand, earth.

灭火注意事项:消防人员须佩戴防毒面具、穿全身消防服

Attention in Fire-extinguishing: The Firemen should put on antigas masks and full fire-fighting suits.

第六部分 泄漏应急处理 Section 6 Accidental release measures

当电池发生泄漏,液体可以用砂,土,或其他惰性物质吸收,受污染的区域应同时通风。

When leakage of batteries happens, liquid could be absorbed with sands, earth, or other inert substance, and the contaminated area should be ventilated meantime.

未放热或燃烧的破损电池,应装入密封的塑料袋或容器。

Damaged batteries that are not hot or burning should be placed in a sealed plastic bag or container.

第七部分 操作处置和储存 Section 7 Handling and storage

操作注意事项:储存时远离食物和水源。吃饭喝水前彻底清洗双手。储有化学物的容器搬用时需防止静电的产生和积聚。

Precautions for safe handling: Consumption of food and beverage should be avoided in work areas. Wash hands with soap and water before eating, drinking. Ground containers when transferring liquid to prevent static accumulation and discharge.

有关火灾及防止爆炸的资料:电池在拆开、挤压、遇火或高温情况下,会引起起火或爆炸,严禁短路或非正确操作。

Information about fire and explosion protection: Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

储存注意事项:储存在一个低温,干燥,通风良好的环境。远离热源,避免长时间阳光照射。未使用时密封容器。

Conditions for safe storage, including any incompatibilities: Requirements to be met by storerooms and receptacles. Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

第八部分 接触控制 / 个人保护 Section 8 Exposure controls/personal protection

最高容许浓度:没有适用标准

Maximum Allowable Concentration: No Standard available

工程控制:操作未破损的电池,没有工程控制要求。对于破损的电池,个人防护用品应包括 化学品防护手套和安全眼镜。

Engineering Controls: no engineering controls are required for handling batteries that have not been damaged. Personal protective equipments for damaged batteries should include chemical resistant gloves and safety glasses.

第九部分 理化特性 Section 9 Physical and Chemical Properties

有关基本物理及化学特性的信息		
Information on basic physical and chemical properties		
外观Appearance	蓝色 Blue	
形状Form	方形 Prismatic	
气味Odour	无味 Odorless	

第十部分 稳定性和反应活性 Section 10 Stability and reactivity

稳定性: 常温常压稳定。

Stability: Stable under normal temperatures and pressures.

禁配物:氧化剂

Incompatibility: oxidizing agents

避免接触的条件: 热和明火、短路和水

Conditions to Avoid: Heat and open flame, short circuit, and water

聚合危害: 不会发生

Hazardous polymerization: Will not occur

分解产物:一氧化碳、二氧化碳、HF、氟磷化物

Decomposition Products: CO,CO2,HF,phosphorus fluoride

第十一部分 毒理性资料

Section 11 Toxicological information

标志及症状: 无,除非电池破裂。

Signs & symptoms: None, unless battery ruptures.

内部物质暴露的情况下,蒸汽烟雾可能对眼睛和皮肤的刺激性。

In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.

吸入:对肺有刺激性。
Inhalation: Lung irritant.
皮肤接触:对皮肤刺激性。
Skin contact: Skin irritant.
眼睛接触:对眼睛有刺激性。
Eye contact: Eye irritant

食入: 吞下中毒。

Ingestion: Poisoning if swallowed.

下列情况下会危险人员身体健康:如果与电池内部材料直接接触,皮肤可能会出现干燥、灼烧等轻微或严重的刺激,并且损坏靶器官的神经,肝脏和肾脏。

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to server irritation, burning and dryness of the skin may occur, Target organs nerves, liver and kidneys.

第十二部分 生态学资料

Section 12 Ecological information

生态毒性: 无

Ecological Toxicity: N/A

生物降解性: 无

Biodegradability: N/A 非生物降解性: 无

Non-biodegradability: N/A

其它有害作用: 该物质对环境有无明显危害。

Other Hazardous: Will not effect environmental evidently.

第十三部分 废弃处置 Section 13 Disposal consideration

废弃处置方法:建议遵照国家和地方法规处置或再利用。

Waste Treatment: Recycle or dispose of in accordance with government, state & local regulations.

废弃注意事项:废电池不能被当作普通垃圾。不能扔进火中或置于高温下。不能解体,刺穿,破碎或类似的处理。最好的办法是回收利用。

Attention for Waste Treatment: Deserted batteries couldn't be treated as ordinary trash.

Couldn't be thrown into fire or placed in high temperature. Couldn't be dissected, pierced, crushed or treated similarly. Best way is recycling.

第十四部分 运输信息 Section 14 Transport information

UN 编号 UN NO.	UN3480
运输专有名称	UN3480 锂离子电池
Proper Shipping Name	UN3480 Lithium Ion Batteries
包装标志 Labels for Package	锂电池操作标签 Lithium Battery Label 9类危险品标签 Class 9 Hazard Label 仅限货机标签 Cargo aircraft Only Label 9
包装等级 Packaging Group	II级

危险品规例规定,运输前,每一个电池设计须通过联合国试验和标准手册38.3节所载的测试。

报告编号: SA2009472U 01001。

The dangerous goods regulations require that each battery design be subject to tests contained in Section 38.3 of the UN Manual of Tests and Criteria prior to being offered for transport.

Report No.: SA2009472U 01001.

危险性分类:

该电池包装应遵守IATA DGR 61版包装说明965的运输要求。

The package of battery should be complied with the requirements of Packing Instruction 965 of IATA DGR 61st Edition for transportation.

该电池包装应遵守IMDG(39-18)或"关于危险货物运输的规章范本" 20th的特殊规定188。

The package of battery should be complied with the requirements of 188 of IMDG (39-18) or the <<Recommendations On The Transport Of Dangerous Goods-Model Regulations>> (20th).

第十五部分 法规信息 Section 15 Regulation information

法规信息:

联合国《关于危险货物运输的建议书规章范本》(20版)、国际航空运输协会 《危险品规则》(60版)、《国际海运危险货物规则》(IMDGCODE)(39-18版)、《国

际危险货物道路运输欧洲协定》(ADR)(2019版)、《国际危险货物铁路运输欧洲协定》(RID)(2019版)

Regulatory information: Recommendations on the transport of dangerous goods-model

Regulations 20th, IATA dangerous goods regulations 60th, International Maritime Dangerous Goods Code (39-18), European Agreement concerning the International Carriage of Dangerous Goods by Road (2019), Regulations concerning the International Carriage of Dangerous Goods by Rail (2019)

第十六部分 其他信息 Section 16 Other information

此信息并非对所有由恒科能源(广东)有限公司的电池均有效。此信息来自可靠来源,但不对所包含信息的完整性和准确性做任何保证。东莞市安磁检测技术有限公司对因电池使用不当造成的任何损坏或损失不承担任何责任,用户应掌握正确的使用方法并对电池的使用负责。

This information is not effective to all the batteries manufactured by Hengke Energy (GuangDong) Co., Ltd This information comes from reliable sources, but no warranty is made to the completeness and accuracy of information contained. Dongguan Anci Electronic Technology Co., Ltd. doesn't assume responsibility for any damage or loss because of misuse of batteries. User's should grasp the correct use method and be responsible for the use of batteries.

Photos of Samples and Labels/样品照片及标识





第11页共11页

声明 Declaration

1. 本报告无批准人、审核人及鉴定人签名无效。

The test report is invalid without the signatures of Ratifier, Reviewer and Testing engineer.

- 2. 对检验报告若有异议,应于收到报告之日起十五天内向检验单位提出。
 Objections to the test report must be submitted to Anci within 15 days.
- 3. 未经本试验室书面同意,不得部分地复制本报告。

Nobody is allowed to photocopy or partly photocopy this test report without written permission of ANCI.

4. 本报告仅对送检样品负责。

The test report is valid for the tested samples only.

5. 本报告涂改无效。

The test report is invalid if altered.

--- 报告结束 ---

--- End of report ---