

WPro8500

8500 Watt Heavy Duty Open Frame Gasoline Portable Generator

8500 Running Watts | 11500 Peak Watts



50 State Model



Lift bracket included for
job site cranes

Fuel efficient, 6.6 gallon
fuel tank that runs 16 hrs
at 25% load

VFT meter displays volts,
frequency, and lifetime hours

Two 5V USB ports for charging
sensitive electronics such as
phones or tablets

OSHA full panel GFCI, 120V
and 240V outlets

Electric start with automatic
choke, battery included

Heavy duty wheels for rough
job site surfaces

SMART IDLE
FOR INCREASED FUEL EFFICIENCY

SINE WAVE OUTPUT
<5% THD
AVR
EQUIPPED
(Less Than 5% Total Harmonic Distortion)



Heavy Duty 13.5 HP 457cc OHV
4-Stroke Westinghouse engine

What Comes in the Box



Control Panel



WPro8500

Heavy Duty Open Frame Generator Specifications



Gasoline Running Watts	8500
Gasoline Peak Watts	11500
Running Amps	71A @ 120V 35A @ 240V
Peak Amps	96A @ 120V 48A @ 240V
AC Voltage	120/240 Volts
DC Voltage	5 Volts
AC Frequency	60 Hz
Parallel Capable	No
Engine Horse Power (HP)	13.5 HP
Total Harmonic Distortion (THD)	<5%
Automatic Voltage Regulator (AVR)	Yes
Smart Idle Control	Yes
Starting System	Electric, Remote, Recoil
Battery Included	Yes
Battery Charger Included	Yes
Remote Start Fob Included	Yes (factory paired)
Remote Start Distance (yards/meters)	109 yd. (100 m.)
Push Button Start	No
Engine Displacement	457cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine RPM	3600
Operational Volume	As low as 74 dBA
Spark Plug (included)	Torch F7TC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140548
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	1.1 qt. (37.2 oz)
Oil Capacity (Quarts/Ounces)	1.1 qt. (37.2 oz)
Low Oil Shutdown	Automatic
Fuel Type	Unleaded Gasoline, 10% Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Material	Steel
Fuel Tank Capacity (Gallons/Liters)	6.6 gal. (25 L)

Run Time at %25 Load (hrs.)	17.5 hrs.
Run Time at %50 Load (hrs.)	12 hrs.
Gasoline Fuel Gauge	Yes
Choke type	Automatic
AC Outlets	(2) Duplex 120V 20A (5-20R), (1) 120V 30A (L5-30R), (1) 120/240V 30A (L14-30R)
DC Outlets	(2) 5V USB ports
Ground	Neutral Bonded to Frame
Covered Outlets	Yes
Transfer Switch Ready	Yes
Westinghouse Portable Transfer Switch Ready	No
Volts, Frequency, Lifetime Hour Meter	Yes
GFCI Outlets	Full Panel GFCI
OSHA Compliant	Yes
LED Data Center	No
RV Ready Outlet	No
Overload Protection (circuit breaker)	Yes
Handle	Yes
Emissions	EPA, CARB
Canada CSA Compliant	No
Heavy Duty Wheel Kit Included	Yes
Wheel Size	10 in diameter, 2.5 in wide
Lifting Bracket	Yes
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years
Commercial Warranty	1 Year
Assembled Length in. (mm)	27.5 in (699 mm)
Assembled Width in. (mm)	27.5 in (699 mm)
Assembled Height in. (mm)	25.5 in (648 mm)
Extended Length in. (mm)	41.5 in (1054 mm)
Carton Length in. (mm)	31 in (787 mm)
Carton Width in. (mm)	22 in (559 mm)
Carton Height in. (mm)	24 in (610 mm)
Dry Unit Weight lb. (kg)	216 lb. (98 kg)
Shipping Weight lb. (kg)	227 lb. (103 kg)
UPC	855464003759

09282018KD
©2018 Westinghouse Outdoor Power Equipment
Specifications are subject to change without notice
Westinghouse Portable Power
777 Manor Park Dr., Columbus, OH 43228

Have questions? Contact our team
at service@wpowereq.com or call
855.944.3571

